

Leverprogramma Stuurventielen Monoblok

Olie: Shell Tellus T37
 Olietemperatuur: 50°C
 Viskositeit: 27 cSt

Type	Werkdruk Bar	Debiet l/min	Drukval P - T Bar
HDM 140/1	320	40	2.5
HDM 11S/1	400	45	2
HDM 11S/2	400	45	3.5
HDM 11S/3	400	45	5
HDM 11S/4	400	45	6
HDM 18/1	400	70	2.5
HDM 18/2	400	70	3
HDM 18/3	400	70	4
HDM 25/1	400	100	2.5
HDM 25/2	400	100	4

Leverprogramma Stuurventielen samenbouw

Type	Werkdruk Bar	Debiet l/min	Drukval P - T Bar
HDS 11/1	320	45	2
HDS 11/3	320	45	5.5
HDS 11/7	320	45	11
HDS 11/10	320	45	16
HDS 15	320	60	3
HDS 15/3	320	60	6
HDS 15/7	320	60	12
HDS 15/10	320	60	14
HDS 20/1	320	80	2
HDS 20/3	320	80	5
HDS 20/7	320	80	12
HDS 20/10	320	80	15
HDS 30/1	320	120	4
HDS 30/3	320	120	9
HDS 30/7	320	120	14
HDS 30/10	320	120	19